

# TECOM-8000

## Conference Phone



### Features

- Digital Signal Processor Design for superior acoustic performance
- Sleek, low profile packaging.
- MUTE (3) buttons located at each corner
- Hold , Flash, Redial & Memory keys
- Backlit LCD display with Caller ID/Call Log
- Digital Volume Control
- Extra long cords provided for placement anywhere in the room.
- Triple- Play design with 3 integrated microphones to accommodate most conference room designs

**T**ECOM-8000 is a high quality conference unit that provides the ultimate in conference room audio performance.

Truly natural sounding conversation can take place when using the TECOM-8000 FDX Conference Phone. This phone has a powerful Digital Signal Processor to accommodate multiple parties that are talking at once.

With integrated microphone pickups, and 3 MUTE operator keys, everyone gets involved in the conference. The microphones are designed to compensate for loud and soft conversation, while eliminating annoying background noise.

# TECOM-8000

## Conference Phone

### Specifications

#### Function Buttons

- MEMORY .....Press to dial a 1-Touch number.
- REMOVE .....Press to delete a redial number, directory or Caller ID entry.
- CALL HISTORY..... Press to review Caller ID entries.
- FLASH .....During a call, press to receive an incoming call, if Call Waiting is activated.
- REDIAL ..... Press to display/redial recently called numbers.
- VOLUME .....Press to adjust ringer or speakerphone volume.
- HOLD .....Press to place call on hold. Press again to continue call.
- SPEAKERPHONE .Press to turn speakerphone on or off (start/end a call)

#### Menu Controls

- DIR .....Press to display, edit or dial phone directory entries.
- MENU/SELECT .....Press to display menu, or to select highlighted menu item. Press and hold<sup>^</sup> or V to scroll rapidly through menus.
- <sup>^</sup>.....Press to scroll up or erase
- v .....Press to scroll down/advance

#### Microphone Controls

- MUTE...Press any of the 3 MUTE buttons to mute all microphones so you can talk privately without your caller hearing you. Press any MUTE button to activate the microphones and resume your telephone conversation.

#### Electrical Specifications

##### Ringer Equivalence Number

- (REN) 0.3B

##### Power Requirement

- Power Adapter Input (120 VAC, 60 Hz, 13 Watts)
- Power Adapter Output (15 VDC, 500 mA)

##### Operating Environment

- Temperature: 0 ~ 40 °C
- Humidity: 10 to 85%, non-condensing

##### Physical Specifications

- Product Weight (Unpackaged)
- 2.0 lbs. (0.9 kg)

##### Product Dimensions

- 12.5" W x 14"L x 3" H (318W x 356L X 76H mm)

Copyright © 2010 Tecom Co., Ltd. All rights reserved. Tecom, Tecom logo are registered trademarks of Tecom Co., Ltd.  
All specifications are subject to change without notice.